

LED CHIPS

LED DRIVER

PHILIPS

LIFUD

The Dalry is a versatile down light used in hotels, restaurants, shops, offices, supermarkets, museums and domestic lighting.

This luminaire comes with a high quality optical diffuser for maximum efficiency without compromising on anti-glare considerations.

- Standard CCT: 4,000K (2,700K / 3,000K / 5,000K options available)
- Cut out dimensions: adapter rings available; Ø150mm - Ø300mm



	15	24	48
Wattage (w)	15	24	48
Lumens (lm)	1675	2575	5225
Luminaire Efficacy	100 ± 5	100 ± 5	105 ± 5
Colour Temp (K)	4000	4000	4000
Beam Angle (°)	35 / 60	35 / 60	35 / 60
CRI	≥80	≥80	≥80
UK Warranty (yrs)	5	5	5
Dimensions (mm)	Ø155	Ø175	Ø245
Cut Out (mm)	> Ø120	> Ø135	> Ø195
Dimmable Option	✓	✓	✓

STANDARDS

EN 60598-1: 2015 Luminaires - General requirements

EN 60598-2-2: 2012 Luminaires. Particular requirements. Recessed luminaires

EN 62493: 2015 Assessment of lighting equipment related to human exposure to electromagnetic field

