



The Fife is an ideal replacement for linear fluorescent luminaires and has been designed for warehouses and supermarkets.

- Tempered frosted PC lens to minimise glare, clear lens also available
- A range of mounting options available
- 2ft, 3ft, 4ft, and 5ft versions available
- 5000K cool white as standard; other colour temperatures available to order 3000K, 4000K, 6000K subject to MOQ
- High quality anodised aluminium heat sink



Wattage (w)	60 - 200
Lumens (lm)	8,400 - 28,000
Efficacy (lm/W)	140 ±5
Dimensions(ft)	2 - 5
Colour Temp (K)	3000 - 6000
CRI	>85
IP Rating	65
UK Warranty (years)	5
Dimmable Option	✓
Emergency Option	✓

STANDARDS

EN 60598-1	Luminaires - General requirements
EN 60598-2-1	Luminaires - Fixed
EN 60598-2-22	Luminaires - Emergency
EN 61347-1	Lamp controlgear - Part 1: General and safety requirements
EN 61347-2-13	Lamp controlgear - Part 2-13: Particular requirements for d.c. or a.c. supplied electronic controlgear for LED modules
EN 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
EN 61547	Equipment for general lighting purposes - EMC immunity requirements
EN 61000-3-2	Electromagnetic compatibility (EMC) - Part 3-2: Limits - for harmonic current emissions
EN 62471	Photobiological safety of lamps and lamp systems
2002/96/EC	Waste Electrical & Electronic Equipment (WEEE)
2011/65/EU	Restriction of the use of certain Hazardous Substances in EEE (RoHS)
(EC) No 1907/2006	The Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

